



NOTE:

1. ALL DIMENSIONS ARE IN MILLIMETERS.
 THE UNSPECIFIED DIMENSION TOLERANCES ARE PLUS/MINUS 0.5.
 ACTIVE AREA DIMENSIONS: 340(L) × 272(W)
 VIEWABLE AREA DIMENSIONS: 340(L) × 272(W)
 PROFILE DIMENSIONS: 388.5(L) × 320.5(W) × 8.2(D).

2. SPECIFICATION:

- ① TECHNICS HOLE: 6-φ 2.5.
- ② DUST-PROOF FRAME, MATERIAL: ALUMINUM.
- ③ 8X19 HOUSING MATES WITH CONTROLLER HOUSING MATERIAL: PBTUL94V-0(BLACK) HOUSING OUTER LAYER MATERIAL: PVCBG01RUBBER.
- ④ CABLE, OUTER LAYER MATERIAL: PVCBG01.
- ⑤ GROUND LINE.
- ⑥ GLASS BOARD, THICKNESS: 6.

CONNECTION CHART

PIN	SIGNAL	INSULATION COLOR
1	GND	OVERALL SHIELD
2	KEY	
3	Y-in2	BLUE
4	Yout	BLUE
5	Y-in1	BLACK
6	GND	YELLOW
7	GND	
8	GND	GREEN
9	X-in2	WHITE
10	Xout	RED
11	X-in1	RED
12	KEY	