



**NOTES**

1. ALL DIMENSION ARE IN MILLIMETERS.
- ② TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN, GLASS IS BEVELED UNDER THE TRANSDUCERS.
- ③ CABLE ROUTING ADDS A MAXIMUM OF 4.0 mm TO INDICATED SECTION OF SCREEN.
- ④ 8X19 HOUSING MATES WITH CONTROLLER.
- ⑤ REFLECTONAL ARRAY AND ② TRANSDUCER ON THE FRONT OF THE GLASS.
- ⑥ CABLE CLIP , MATERIAL:METAL.
- ⑦ SAFETY GLASS BOARD.
- ⑧ CABLE, OUTER LAYER MATERIAL: PVC6G01,
- 9 THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.

**CONNECTION CHART**

PIN	SIGNAL	INSULATION COLOR OVERALL SHIELD
1	GND	
2	NC	
3	Y-in2	BLUE
4	Y-out	BLUE
5	Y-in1	BLACK
6	GND	YELLOW
7	GND	
8	GND	GREEN
9	X-in2	WHITE
10	X-out	RED
11	X-in1	RED
12	NC	